



P03U



P03UB



P03UW




RE-USABLE EARPLUG WITH SAFETY CORD.

SNR: 31dB

Std = Standard Deviation APV = Assumed Protection Value H = High frequency attenuation value M = Medium frequency attenuation value L = Low frequency attenuation value Tested according to EN352-2	Dome diameter range: 8-12mm								H:31dB M:29dB L:28dB				
	f/Hz	63	125	250	500	1000	2000	4000	8000				
	Mean (dB)	33,6	30,5	32,9	33,4	32,2	35,7	40,1	45,9				
	StD (dB)	4,5	3,8	4,3	4,7	5,2	6,2	5,6	4,8				
	APV (dB)	29,1	26,7	28,6	28,7	27	29,5	34,5	41,4				

INSTRUCTIONS:



PULL TO UNCOIL



LIFT EARLOBE & INSERT

CHECK FOR CORRECT FIT

CLEAN USING MILD SOAP AND WATER

RETURN USED PLUXONE FOR RECYCLING



NO. 1 FOR COST, COMFORT, SAFETY & HYGIENE



LOWER COSTS



LOWEST UNIT COST, CAN LAST LONGER EASY & FAST CLEANING

BETTER COMFORT




SOFT EARPIECES SOFT FLEXIBLE CORD

BETTER SAFETY & HYGIENE

**+** HYGIENIC DESIGN



SINGLE FLEXIBLE PART SMOOTH & NO GAPS EASY TO CLEAN AND DRY.



HYGIENIC AUTOMATED MANUFACTURING




FOOD SAFETY PERSONAL HYGIENE

NO DISCONNECTING IF PULLED



FOOD SAFETY LASTS LONGER

SAFETY CORD YIELDS IF CAUGHT UP



PERSONAL SAFETY SAFE TO USE @ MACHINES

Old technology corded earplugs




EXPENSIVE OLD TECH FALLS APART PREMATURELY CLEANING NIGHTMARE




HARD / TOO BIG EARPLUGS SOME CORDS ARE HARD

BACTERIA TRAPS, CANNOT CLEAN & DRY: IDEAL FOR BACTERIA GROWTH



BRAIDED CORDS & CONNECTIONS




HAND CONTACT MANUFACTURING



FOOD SAFETY RISK PERSONAL HEALTH RISK

DISCONNECTS IF PULLED +-9mm



FOREIGN OBJECT RISK AT FOOD PLANTS

BRAIDED AND EXTRUDED CORDS DOES NOT YIELD IF CAUGHT UP.



LETHAL RISK



DO NOT USE @ MACHINES